



art & science of
amazing protection



Moo-ve Over Ordinary Gloves,
ASAP Has You ***Covered!***

Series No.:
20840 X-Tra Thick X-Tended Black Nitrile Powder Free Examination Gloves



BENEFITS OF X-TRA THICK X-TENDED BLACK NITRILE POWDER FREE GLOVES

Extended Length: The gloves' extended length not only covers the hands but also offers additional protection up the forearm. This feature is particularly beneficial for tasks that involve immersion in liquids or exposure to splashes, providing users with an extra layer of defence.

Full Hand Texture: The gloves feature a comprehensive micro texture across the entire hand, improving grip in both wet and dry conditions. This full-hand texture enhances user dexterity and control, allowing for precise handling of tools and equipment.

Professional Black Colour: The sleek **black** colour of the gloves provides a stark contrast against contaminants, aiding in the detection of substances such as mastitis in dairy farming. This feature ensures a professional appearance while enhancing the functionality of the gloves in various industrial settings.

Enhanced Durability: The gloves' thicker construction provides added durability, offering increased resistance to punctures, tears, and chemical exposure. This feature ensures that the gloves can withstand prolonged use and tougher tasks without compromising on protection.

Versatile Applications: The gloves' robust design and compliance with safety standards make them suitable for a wide range of industries. From agriculture to automotive, manufacturing to medical, these gloves are versatile enough to meet the needs of various professional applications.

Compliance with Regulations: Our gloves meet and exceed various regulatory standards, including medical device, PPE, and food safety regulations. This compliance reassures users of the gloves' quality and safety, allowing them to perform their tasks with confidence.

Regulations

- Medical Device Regulation (EU) 2017/745
- PPE Regulation (EU) 2016/425
- Food Contact Regulation (EU) 2020/1245 of Regulation (EU) No 10/2011
- REACH Regulation

Harmonized Standards

- EN ISO 21420:2020
- EN 374-1:2016+A1:2018
- EN 374-4:2019
- EN 374-5:2016
- EN 455-1:2020
- EN 455-2:2015
- EN 455-3:2015
- EN 455-4:2019

Quality Assurance

- ISO 9001:2015
- ISO 13485:2016
- ISO 14001:2015



At ASAP, we are committed to hygiene control and quality assurance. Proper hygiene standard is practiced throughout the development of all ASAP products from raw materials handling, processing, production, inspection, to our finished product to deliver high quality products while limiting risk of cross-contamination.

Look for the Hygiene Matters™ logo, quality and hygiene you can trust.

X-TRA THICK X-TENDED NITRILE POWDER FREE EXAMINATION GLOVES



Colour Option:



Agriculture



Safety



Automotive



Series No.:

20840 X-Tra Thick X-Tended Black Nitrile Powder Free Examination Gloves

Series Size Codes

Small	Medium	Large	Extra Large
S, 7	M, 8	L, 9	XL, 10
20842	20843	20844	20845

Product Specifications

Design	Ambidextrous, Textured Surface, Beaded Cuff
Colour	Black
Acceptance Quality Level (AQL)	1.5
Packing Mode	50 pcs per box, 10 boxes per carton

Dimension Specifications

Glove Size	Palm Width (mm)	Length (mm)	Thickness Single Wall (mm)		
		EN 455	Cuff (25±5 from bead)	Palm (centre of palm)	Finger (13±3 from tip)
S, 7	85 ± 5	Min. 290	0.11 ± 0.02	0.14± 0.02	0.15 ± 0.02
M, 8	95 ± 5				
L, 9	105 ± 5				
XL, 10	115 ± 5				

Physical Properties Specifications

	EN 455 Force at Break (N)
Before Aging	Min. 6.0, Median >9N
After Aging	Min. 6.0, Median >9N

Packaging Dimensions

Inner	235 x 125 x 70mm
Carton	370 x 258 x 245 mm

Powder Residue

Powder Free (mg/glove)	Max. 2
------------------------	--------

Instructions For Use

Description - X-Tra Thick X-Tended Nitrile Powder Free Examination Gloves, Non-sterile, Single Use Only.

Intended Use - ASAP X-Tra Thick X-Tended nitrile glove is a disposable glove product worn to protect the hand of wearer against mechanical action whose effects are superficial, cleaning materials of weak action and easily reversible effects.

How To Don Gloves - Inspect the gloves to ensure there are no pinholes or tears. If gloves are ambidextrous, they can be worn on either hand. If not, align the glove's fingers and thumb with the proper hand before donning. Insert five fingers into the cuff and pull the cuff over the wrist. Check for a secure fit around the fingers and palm. The cuff should fit snugly around the wrist.

How To Doff Gloves - After use, users should visually check the glove and remove any contamination from the outer surface before removing the gloves from the hands. Grasp the outside edge of the glove near the wrist. Peel the glove away from the hand, turning it inside out. Hold it in the opposite glove hand. Slide an ungloved finger under the wrist of the remaining glove, be careful not to touch the outside of the glove. Peel the remaining glove off from the inside, creating a "bag" containing both gloves. Discard.

Disposal - Properly dispose of all used nitrile glove. Follow your institution's policies for use and disposal of these gloves.

Storage - Store in a dry place. Avoid excessive heat (30°C). Exposed product should be shielded from direct sunlight, intense artificial light, x-ray machines, and other source of ozone.

Shelf Life - Three years from the manufacturing date.

Warning - These gloves are for single and transient use only.

Caution - This information does not reflect the actual duration of protection in the workplace and the differentiation between mixtures and pure chemicals. The chemical resistance has been assessed under laboratory conditions from samples taken from the palm only (except in cases where the glove is equal or over 400mm - where the cuff is also tested) and relates only to the chemical tested.

It can be different if the chemical is used in a mixture. It is recommended to check that the gloves are suitable for the intended use because the conditions at the workplace may differ from the type test depending on the temperature, abrasion, and degradation. When used, protective gloves may provide less resistance to the dangerous chemical due to changes in the physical properties. Movements, snagging, rubbing, degradation caused by the chemical contact etc. may reduce the actual use time significantly.

For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. This product contains nitrile rubber, which may cause allergic reactions in individuals who are known or suspected to be allergic to nitrile rubber. If an allergic reaction occurs, stop using immediately and consult a physician. This product is not made of natural rubber latex.

EN ISO 374

Chemical Permeation (EN ISO 374-1:2016+A1:2018/Type C)	Level	Mean Degradation % (EN ISO 374-4:2019)	
K 40% Sodium Hydroxide	6	-10.9	Degradation levels indicate the change in Puncture Resistance of the glove after exposure to the challenge chemical.
P 30% Hydrogen Peroxide	1	11.5	
T 37% Formaldehyde	5	4.2	

EN ISO 374

EN 16523-1:2015+A1:2018 Classification of Permeation Performance Level

Measured Breakthrough Time (min)	>10	> 30	> 60	> 120	> 240	> 480
Permeation Performance Level	1	2	3	4	5	6

The penetration levels have been assessed under laboratory conditions and relates only to the tested specimen.

Resistance against Bacteria and Fungi - PASS
Resistance against Virus - PASS

ASAP INTERNATIONAL SDN BHD
No. 1, Jalan Sitar 33/6, Seksyen 33,
40400 Shah Alam, Selangor,
Malaysia.

T : +603 5191 0166
F : +603 5191 0702
E : info@whyasap.com
W : www.whyasap.com

ASAP INNOVATIONS LTD.
Unit 7, The Courtyard,
Fonthill Business Park,
Fonthill Road, Dublin,
D22 XA07, Ireland.

T : +353 1466 1660
E : info@whyasap.ie
W : www.whyasap.ie

ASAP INNOVATIONS (UK) LTD.
13, Diamond Court,
Opal Drive, Fox Milne,
Milton Keynes,
MK15 0DU, United Kingdom.

T : +44 (0) 1908 732700
E : info@whyasap.co.uk
W : www.whyasap.co.uk

